> BIRDIE EV and BIRDIE PLUS EV

Multiparameter system that combines electrical switchboard, salt chlorination and pH regulation. Ideal for private, public and commercial pools up to 240 m³.

- > IntelliFilter™ auto running cycle calculation based on water °C
- > PowerBoost™ auto increase the daily cycle period if water is >25°C
- > WinterSave™ auto reduce weakly cycles if water is <10°C *
- > Water Level Kit for automatic water level regulation (optional)
- > ORP Kit for automatic chlorine level regulation (optional)
- > Electronic Heating Kit for automatic water heating control
- > Electronic Lights Kit for automatic pool lights control
- > Peristaltic or electromagnetic pH injection pump
- > Electronic electrolysis time meter
- > Electronic cover detector and electronic flow detector

* (Up to 50% energy savings during the winter period)

| Specifications |

Power Supply: 220/240Vac 50/60Hz Cell: Self cleaning monopolar MMO coating Cell Assembly: vertical and horizontal Cell connections: ø63mm (ø50mm adaptor) Cell Lifetime: 12.500h* (longest in the market) Salinity Range: 3 to 5 Kg/m³ (possible adjustment) Water Flow: From 5 m³/h to 30 m³/h Water Pressure: Tested at 5 Bar Water Temperature Range: 12°C to 40°C Room Temperature: Tested at 50°C Reverse Polarity: 3h to 8h Cooling: forced with ventilation w300mm X H400mm X L200mm н**315**mm **Ø63**m Warranty: 5 Years Electronic / 4 Years Cell

* Lifetime can vary based on the salinity level, reverse polarity running cycle and water chemical balance.

















Temperature

Circulation Pump Management Management

Control

Warranty



BIRDIE EV MODELS

CODE 100001194 ^A	MODEL Birdie EV10	CHLORINE PRODUCTION g/h 10	pH PUMP Peristaltic	pH INJECTION (/h 4.5-2
CODE 100001195 ^A	MODEL Birdie EV15	CHLORINE PRODUCTION g/h 15	pH PUMP Peristaltic	pH INJECTION I/h 4.5-2
CODE 100001196 ^A	MODEL Birdie EV 20	CHLORINE PRODUCTION g/h 20	рН РИМР Peristaltic	pH INJECTION (/h 4.5-2
CODE 100001197 ^A	MODEL Birdie EV30	CHLORINE PRODUCTION g/h 30	pH PUMP Peristaltic	pH INJECTION (/h 4.5-2
CODE 100001198 ^A	MODEL Birdie EV40	CHLORINE PRODUCTION g/h 40	pH PUMP Peristaltic	pH INJECTION (/h 4.5-2

BIRDIE PLUS EV MODELOS

CODE 100001199 ^A	MODEL Birdie PLUS EV 10	CHLORINE PRODUCTION g/L 10	pH PUMP Electromagnetic	pH INJECTION (/h 6-7
CODE 100001200 ^A	MODEL Birdie PLUS EV 15	CHLORINE PRODUCTION g/L 15	pH PUMP Electromagnetic	pH INJECTION (/h 6-7
CODE 100001201 ^A	MODEL Birdie PLUS EV 20	CHLORINE PRODUCTION g/L 20	pH PUMP Electromagnetic	pH INJECTION (/h 6-7
CODE 100001202 ^A	MODEL Birdie PLUS EV 30	CHLORINE PRODUCTION g/L 30	pH PUMP Electromagnetic	pH INJECTION (/h 6-7
CODE 100001203 ^A	MODEL Birdie PLUS EV 40	CHLORINE PRODUCTION g/L 40	pH PUMP Electromagnetic	pH INJECTION I/h 6-7

OPTIONAL

CODE 100000866 ^A	MODEL ORP KIT	DESCRIPTION Redox system for reading and regulating the level of chlorine in water
CODE 100000729 ^A	MODEL Levels KIT	DESCRIPTION Automatic water level regulator including sensors and electro valve

accessories













ORP KIT

Level KIT