

Multiparameter system that combines electrical switchboard, salt electrolysis, salt chlorination and pH regulation, lights control and heating in one device. Ideal for private, public and commercial pools.

- > **WinterSave TM** - auto reduce weakly cycles period if water is < 15°C
- > **Power Boost TM** - auto increase the daily cycle period if water is > 25°
- > **IntelliFilter TM** - auto running cycle calculation based on water °C
- > Electronic heating Kit for automatic water heating control
- > Electronic Lights Kit for automatic pool lights control
- > Water Level Kit for automatic water level regulation (optional)
- > ORP Kit for automatic chlorine level regulation (optional)
- > Peristaltic or electromagnetic ph injection pump
- > Electronic cover and flow detector
- > Electronic electrolysis time meter

* (up to 50% energy savings during the winter period)

| Specifications |


Power Supply: 220/240VAC 50/60Hz
Cell: Self cleaning monopoly MMO coating
Cell Assembly: Vertical and horizontal
Cell Connections: ø63mm or ø50 mm (reduction rings included)
Cell lifetime: 12.500h* (longest in the market)
Salinity Range: 3 to 5 Kg/m3 (possible adjustment)
Water Flow: From 5 m³/h to 30 m³/h
Water Pressure: Tested at 5 Bar
Water Temperature Range: From 12°C to 40°C
Room Temperature: Tested at 50°C
Reverse Polarity: 3h to 8h
Cooling: Forced with ventilation
Warranty: 2 Years



* Lifetime can vary based on the salinity level, reverse polarity running cycle and water chemical balance.



Large Volume
Pools




Hours



Temperature
Sensor



pH Sensor




ORP Sensor




Circulation
Pump Management



Water Level
Management



Warranty



BIRDIE PRO MODELS

CODE 100001612	MODEL Birdie Pro 60G	POOL VOLUME 60 g/h
CODE 100001526	MODEL Birdie Pro 80G	POOL VOLUME 80 g/h
CODE 100001632	MODEL Birdie Pro 120G	POOL VOLUME 120 g/h
CODE 100001633	MODEL Birdie Pro 160G	POOL VOLUME 160 g/h